



MASI20 INSTALLATION TECHNOLOGY

Distributor 2x AS-I and 3x extern power

3 AS-Interface + 2 power ports  
5 plug terminals included

[Link a termékhez](#)

Ábrák



Szimbolikus ábra



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27279219 |
| ECLASS-6.1      | 27279219 |
| ECLASS-7.0      | 27279219 |
| ECLASS-8.0      | 27279219 |
| ECLASS-9.0      | 27440108 |
| ECLASS-10.1     | 27440111 |
| ECLASS-11.1     | 27440111 |
| ECLASS-12.0     | 27440111 |

|                       |               |
|-----------------------|---------------|
| ETIM-5.0              | EC001596      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879050494 |
| Packaging unit        | 1             |

**Electrical data | Supply**

|                                 |      |
|---------------------------------|------|
| Operating voltage DC max.       | 36 V |
| Current operating per port max. | 8 A  |
| Total current max.              | 24 A |

**Device protection | Electrical**

|                                     |       |
|-------------------------------------|-------|
| Degree of protection (EN IEC 60529) | IP20  |
| Insulation strength ASI/Power       | 200 V |

**Mechanical data | Mounting data**

|                            |                           |
|----------------------------|---------------------------|
| Mounting method            | geschnappt                |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height                     | 52 mm                     |
| Width                      | 67 mm                     |
| Depth                      | 90 mm                     |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C  |

**Conformity**

|                  |            |
|------------------|------------|
| Product standard | EN 60664-1 |
|------------------|------------|

**Connection type 3**

|                          |                    |
|--------------------------|--------------------|
| Connection type 1        | Asi Bus            |
| Connection type 2        | Power              |
| Connection type 3        | Power / Asi        |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 2                  |
| PIN 1                    | A +                |
| PIN 2                    | A -                |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 2                  |
| PIN 1                    | Power +            |
| PIN 2                    | Power -            |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 4                  |
| PIN 1                    | Power +            |
| PIN 2                    | Power -            |
| PIN 3                    | AS-i +             |
| PIN 4                    | AS-i -             |