

6 TX managed switch with Gigabit

+ 4 power M12 IP67


6-port managed IP 67 gigabit switch, 4 power ports
6 Gigabit ports
4 power ports, A-coded
Connection cables are in the online shop under "Connection Technology".

Link a termékhez

Ábrák



Szimbolikus ábra



Commercial data	
ECLASS-11.1	19170401
customs tariff number	85176200
GTIN	4048879852289
Packaging unit	1
Electrical data Supply	
Operating voltage DC min.	18 V
Operating voltage DC max.	28 V
Industrial communication	
Data transmission rate max.	2500 MBit/s
Industrial communication Ethernet functionality	
Auto-crossover	yes
Auto-negotiation	yes
duplex	Full duplex
LLDP frames	forwarding
Ring topology	RSTP, STP
Switch type	managed
Industrial communication IIoT functions	
Webserver	HTTP, HTTPS
Switch Management	

Addressing	BOOTP/DHCP client, DCP, SSH-Befehlszeile
NAT	1:1
RSTP (IEEE 802.1D-2004, IEC 62439-1)	Default on
Simple Network Management Protocol (SNMP)	v1 + v2c + v3 (default active)
VLAN managed (IEEE 802.1Q)	yes
VLANs max. (IEEE 802.1Q)	64
Time synchronization	NTP client
Diagnostics	
Alarm contact	no
Diagnostic	No voltage
Remote maintenance	Open VPN client
LED display	Ethernet connection/data traffic
Port mirroring	1:1
RMON	yes
SNMP traps	yes
Syslog	yes
Installation Connection	
Number ports	6
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP67
Mechanical data Material data	
Material housing	Metal
Mechanical data Mounting data	
Suitable for mounting type	2-hole screw mounting
Height	225 mm
Width	63 mm
Depth	42 mm
Environmental characteristics Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	45 °C