

LED-INDICATOR OPAC / RED

LED-24V IP65


(red)
24 V AC/DC
The modules are suitable for wall thickness of 1.5...5.0 mm.

Link a termékhez

Ábrák



Szimbolikus ábra



Commercial data	
ECLASS-6.0	27261590
ECLASS-6.1	27261501
ECLASS-7.0	27261501
ECLASS-8.0	27261501
ECLASS-9.0	27261501
ECLASS-10.1	27261501
ECLASS-11.1	27261501
ECLASS-12.0	27261501
ETIM-5.0	EC000272
customs tariff number	85318070
GTIN	4048879041331
Packaging unit	10
Electrical data Supply	
Operating voltage AC	24 V
Operating voltage AC min.	20,4 V
Operating voltage AC max.	26,4 V
Operating voltage DC	24 V
Operating voltage DC min.	20,4 V
Operating voltage DC max.	26,4 V
Current consumption min.	8 mA
Current consumption max.	12 mA
Installation Connection	
Connection information	Faston 2.8×0.8 mm
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP65

Device protection Media	
Flame resistance	flame retardant
Mechanical data	
Diameter LED	5 mm
Mechanical data Material data	
Material housing	Plastic
Mechanical data Mounting data	
Diameter front panel drilling	9 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	50 °C