MURR ELEKTRONIK
stay connected

MSDD-AU7AB 1LED DIREKTANSCHL.F.M.-VENTIL

24 V AC/DC ±25%
LED and suppressor diode
4-pole
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link a termékhez

Ábrák







Szimbolikus ábra

Commercial data	
ECLASS-6.0	27143423
ECLASS-7.0	27449001
ECLASS-8.0	27449001
ECLASS-9.0	27440321
ETIM-5.0	EC001855
customs tariff number	85366990
GTIN	4048879238052
Packaging unit	50

Electrical data | Supply	
Operating voltage AC	24 V

A jelen adatlapban található adatokat a lehető legnagyobb gondossággal dolgozták ki.
Felelősségünk az adatok helyességéért, teljeskörűségéért és aktualitásáért a súlyos vétkesség esetére korlátozódik. Állapot: 17.05.2024

MURR ELEKTRONIK
stay connected

Operating voltage AC min.	18 V
Operating voltage AC max.	30 V
Operating voltage DC	24 V
Operating voltage DC min.	18 V
Operating voltage DC max.	30 V
Current operating per contact max.	4 A
Diagnostics	
Status indication LED	yellow
Installation | Connection	
Tightening torque	0,6 Nm
Mounting set	M12 x 1
Installation | Pin assignment	
No. of poles	2 + PE
Device protection | Electrical	
Additional suppressor	Suppressor diode
Mechanical data | Mounting data	
Mounting method	inserted, screwed
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	85 °C
Important installation notes	
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
Note on bending radius	**Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.

A jelen adatlapban található adatokat a lehető legnagyobb gondossággal dolgozták ki.
Felelősségünk az adatok helyességéért, teljeskörűségéért és aktualitásáért a súlyos vétkesség esetére korlátozódik. Állapot: 17.05.2024