

MASI00 WITH CONNECTION CABLE



4 digital inputs , 4 digital outputs

Digital inputs/outputs

DI4/DO4 - 0.2 A

I/O cable 250 mm

IP00

[Link a termékhez](#)**Ábrák**

Szimbolikus ábra

Commercial data

ECLASS-6.0	27242604
ECLASS-7.0	27242604
ECLASS-8.0	27242604
ECLASS-9.0	27242604
ETIM-5.0	EC001599
customs tariff number	85176200
GTIN	4048879046466
Packaging unit	1

Electrical data | Supply

Bus voltage AS-Interface DC min.	26,5 V
----------------------------------	--------

Bus voltage AS-Interface DC max.	31,6 V
Current consumption AS-i port max.	250 mA
Total current max.	0,2 A
Electrical data Input	
Overload resistant	yes
Short-circuit protected	yes
Type input	for standard switches
Current carrying capacity max.	0,2 A
Electrical data Output	
Switch off time in case of short circuit	50 ms
Overload resistant	yes
Short-circuit protected	yes
Switching current max.	30 mA
Industrial communication Bus data	
Address setting type	Plug-in terminal
Industrial communication AS-Interface	
Profile (IO.ID.ID2)	S-7.F.F
Diagnostics	
Diagnostic	No voltage
Diagnostic via LED	per module
LED display	Ethernet connection/data traffic
Installation	
Connection cross section min.	0,2 mm ²
Connection cross section max.	2,5 mm ²
Installation Connection	
Connection	Screw plug-in terminals
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP00
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	43 mm
Width	15 mm
Depth	81 mm
Environmental characteristics Climatic	
Operating temperature min.	0 °C
Operating temperature max.	55 °C
Storage temperature min.	-20 °C
Storage temperature max.	70 °C
Connection type 2	
Connection type 1	Asi Bus
Connection type 2	I / O
Connection	Screw terminals SK
Family construction form	terminal
Gender	male
Color contact carrier	green
No. of poles	2
PIN 1	A +
PIN 2	A -
Connection	Plug-in terminals RK

Family construction form	terminal
Gender	male
Color contact carrier	black
No. of poles	10
PIN 1	0 V
PIN 2	U +
PIN 3	0 0
PIN 4	I 0
PIN 5	0 1
PIN 6	I 1
PIN 7	0 2
PIN 8	I 2
PIN 9	0 3
PIN 10	I 3