

MVP12, 6XM12, MOSA, PLUGGABLE CABLE

10.0m PUR-JB 12x0,34+5x0,75

6-way, 5-pole, MOSA  
PUR/PVC (UL/CSA)  
10.0 m  
potentially separated  
with LED for digital PNP-signals 24 V DC  
quick connection elements included

[Link a termékhez](#)

Ábrák



Szimbolikus ábra

| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27279219 |
| ECLASS-6.1      | 27279219 |
| ECLASS-7.0      | 27279219 |
| ECLASS-8.0      | 27279219 |
| ECLASS-9.0      | 27440108 |
| ECLASS-10.1     | 27440108 |
| ECLASS-11.1     | 27440108 |
| ECLASS-12.0     | 27440108 |

|                                                 |                      |
|-------------------------------------------------|----------------------|
| ETIM-5.0                                        | EC002585             |
| customs tariff number                           | 85369010             |
| GTIN                                            | 4048879057592        |
| Packaging unit                                  | 1                    |
| <b>Electrical data   Supply</b>                 |                      |
| Operating voltage DC                            | 24 V                 |
| Current operating per contact max.              | 4 A                  |
| Total current at 1 time current feed-in max.    | 8 A                  |
| Total current at 2 times current feed-in max.   | 16 A                 |
| <b>Industrial communication</b>                 |                      |
| Number of signals per port                      | 2                    |
| <b>Installation</b>                             |                      |
| Connection cross section min.                   | 0,25 mm <sup>2</sup> |
| Connection cross section max.                   | 0,5 mm <sup>2</sup>  |
| <b>Device protection   Electrical</b>           |                      |
| Degree of protection (EN IEC 60529)             | IP67                 |
| Additional condition protection degree          | screwed, mounted     |
| <b>Device protection   Media</b>                |                      |
| Flame resistance                                | flame retardant      |
| <b>Mechanical data   Material data</b>          |                      |
| Material housing                                | Plastic              |
| <b>Mechanical data   Mounting data</b>          |                      |
| Mounting method                                 | Cap nut              |
| Height                                          | 43 mm                |
| Width                                           | 50,2 mm              |
| Depth                                           | 122 mm               |
| <b>Environmental characteristics   Climatic</b> |                      |
| Operating temperature min.                      | -20 °C               |
| Operating temperature max.                      | 80 °C                |