



**MET 1-PHASE CONTROL AND ISOLATION TRANSFORMER**

P: 2000VA IN: 230VAC+/- 5% OUT: 230VAC

Single-phase - Control and Isolation Transformers  
2000 VA  
Spring clamp terminals  
Isolation class T 40/B

[Link a termékhez](#)

**Ábrák**



Szimbolikus ábra



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27031302 |
| ECLASS-6.1      | 27031302 |
| ECLASS-7.0      | 27031302 |
| ECLASS-8.0      | 27031302 |
| ECLASS-9.0      | 27031302 |
| ECLASS-10.1     | 27031302 |

|                       |               |
|-----------------------|---------------|
| ECLASS-11.1           | 27031302      |
| ECLASS-12.0           | 27031302      |
| ETIM-5.0              | EC002486      |
| customs tariff number | 85043200      |
| GTIN                  | 4048879066327 |
| Packaging unit        | 1             |

**Electrical data | Supply**

|                 |              |
|-----------------|--------------|
| Power frequency | 50 ... 60 Hz |
|-----------------|--------------|

**Electrical data | Input**

|                       |         |
|-----------------------|---------|
| Input voltage AC      | 230 V   |
| Input voltage AC min. | 218,5 V |
| Input voltage AC max. | 241,5 V |
| Current input AC      | 9,2 A   |
| Max. inrush current   | 142,2 A |
| Short-circuit current | 334,8 A |

**Electrical data | Output**

|                           |         |
|---------------------------|---------|
| Output voltage AC         | 230 V   |
| Output voltage adjustable | no      |
| Power rating AC max.      | 2000 VA |

**Device protection | Electrical**

|                                        |      |
|----------------------------------------|------|
| Insulation test voltage input - output | 4 kV |
|----------------------------------------|------|

**Mechanical data | Mounting data**

|                            |                    |
|----------------------------|--------------------|
| Suitable for mounting type | Long-hole mounting |
| Mounting dimension a       | 200 mm             |
| Mounting dimension b       | 174 mm             |
| Mounting dimension c       | 9 mm               |
| Height                     | 170 mm             |
| Width                      | 195 mm             |
| Depth                      | 250 mm             |
| Diameter bore              | 9 mm               |
| Length bore                | 14 mm              |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 40 °C  |
| Storage temperature min.   | -40 °C |
| Storage temperature max.   | 80 °C  |

**Conformity**

|                  |                                               |
|------------------|-----------------------------------------------|
| Product standard | EN 61558-1, EN 61558-2-4, EN 62041 category 0 |
|------------------|-----------------------------------------------|