

**MODLINK MSDD DATA INSERT**

2×USB-A female/female + 1×RJ45 + 1×RJ12

RJ45; RJ12; USB; USB (A)  
1× RJ45, 8-pole metal, CAT5e (female/female)  
1× RJ12 (6-pole plastic)  
2× USB (female/female) form A

[Link a termékhez](#)

Ábrák



Szimbolikus ábra



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27189217      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC002625      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879037839 |
| Packaging unit                           | 1             |
| Mechanical data   Mounting data          |               |
| Height                                   | 88 mm         |
| Width                                    | 51 mm         |
| Depth                                    | 70,4 mm       |
| Environmental characteristics   Climatic |               |
| Storage temperature min.                 | -10 °C        |
| Storage temperature max.                 | 60 °C         |
| Shielding plate                          |               |

|                                       |                   |
|---------------------------------------|-------------------|
| Connection information                | Threaded hole M4  |
| Tightening torque                     | 0,9 Nm            |
| <b>USB</b>                            |                   |
| Operating voltage AC                  | 48 V              |
| Operating voltage DC                  | 48 V              |
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Operating current                     | 1,5 A             |
| USB specification                     | 3.0               |
| Data transmission rate max.           | 5000 MBit/s       |
| Looking techniques                    | Snap-in connector |
| <b>RJ12</b>                           |                   |
| Operating voltage AC max.             | 48 V              |
| Operating voltage DC max.             | 48 V              |
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Operating current max.                | 1 A               |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ12              |
| Family type Back side                 | RJ12              |
| Looking techniques                    | Snap-in connector |
| <b>RJ45</b>                           |                   |
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat5e             |
| Looking techniques                    | Snap-in connector |