

COMLIGHT56 LED BLUE STATUS LIGHT

Input 24VDC

Compact status light  
blue

[Link a termékhez](#)

Ábrák



Szimbolikus ábra



| Commercial data                        |                  |
|----------------------------------------|------------------|
| ECLASS-6.0                             | 27371220         |
| ECLASS-6.1                             | 27110390         |
| ECLASS-7.0                             | 27110390         |
| ECLASS-8.0                             | 27110390         |
| ECLASS-9.0                             | 27110350         |
| ECLASS-10.1                            | 27110350         |
| ECLASS-11.1                            | 27110350         |
| ECLASS-12.0                            | 27110350         |
| ETIM-5.0                               | EC000232         |
| customs tariff number                  | 85319000         |
| GTIN                                   | 4048879853873    |
| Packaging unit                         | 1                |
| Electrical data   Supply               |                  |
| Operating voltage DC                   | 24 V             |
| Current consumption max.               | 26 mA            |
| Industrial communication   HMI         |                  |
| Luminous intensity                     | 239 mcd          |
| Device protection   Electrical         |                  |
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |
| Mechanical data   Material data        |                  |

Material housing Plastic

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 61 mm |
| Width  | 56 mm |
| Depth  | 56 mm |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 50 °C  |

**Connection type 1**

|                          |                           |
|--------------------------|---------------------------|
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| No. of poles             | 2                         |
| PIN 1                    | 24 V DC (0 V)             |
| PIN 2                    | 0 V (24 V DC)             |