

Signal tower Modlight70 Pro equipped with LED modules

green,amber,red,buzzer,M12 plug downward


Basic, buzzer, flash + LED modules + M12 (down)
green, yellow, red

Link a termékhez

Ábrák



Szimbolikus ábra



Commercial data	
ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-8.0	27371230
ECLASS-9.0	27371230
ECLASS-10.1	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ETIM-5.0	EC001042
customs tariff number	85318070
GTIN	4048879759939
Packaging unit	1
Electrical data Supply	
Operating voltage DC	24 V
Operating voltage DC min.	21,6 V
Operating voltage DC max.	26,4 V
Current consumption max.	385 mA
Industrial communication HMI	
Buzzer sound	fast beep, continuous beep, fast high-low, sweep tone
Reduced sound pressure at 1 m	80 dB
Sound pressure at 1 m	90 dB
HMI Illumination properties	

A jelen adatlapban található adatokat a lehető legnagyobb gondossággal dolgozták ki.
Felelősségünk az adatok helyességéért, teljességéért és aktualitásáért a súlyos vétkesség esetére korlátozódik. Állapot: 05.05.2024
Murrelektronik Kft. | Közép utca 16 | H- 9024 Győr | Telefon: +36 96 900-125 | Telefax: +36 96 900-127 | shop@murrelektronik.hu | shop.murrelektronik.hu

Blink cycles 60 ±12 per minute

Device protection | Electrical

Degree of protection (EN IEC 60529) IP65
Additional condition protection degree inserted, locked

Mechanical data | Material data

Color housing black
Material housing Plastic

Mechanical data | Mounting data

Height 293 mm
Width 70 mm
Depth 70 mm

Environmental characteristics | Climatic

Operating temperature min. -30 °C
Operating temperature max. 60 °C