

Female module, 4-pole, crimp t.

830 V, 40 A


Female
4-pole
Crimp
Technical data will be only guaranteed with Murrelektronik components.

Link a termékhez

Ábrák



Szimbolikus ábra



Commercial data	
ECLASS-6.0	27143424
ECLASS-6.1	27261204
ECLASS-7.0	27440204
ECLASS-8.0	27440204
ECLASS-9.0	27440217
ECLASS-10.1	27440217
ECLASS-11.1	27440217
ECLASS-12.0	27440217
ETIM-5.0	EC000438
customs tariff number	85389099
GTIN	4048879641609
Packaging unit	5
Electrical data Supply	
Operating voltage AC	830 V
Operating voltage DC	830 V
Operating current	40 A
Installation	
Connection cross section min.	1,5 mm²
Connection cross section max.	6 mm²
AWG number min.	16

AWG number max. 10

Installation | Connection

Wire insulation diameter min. 5,2 mm

Connection Crimp

Gender female

Mating cycles min. 500

Installation | Pin assignment

No. of poles 4

Device protection | Electrical

Pollution Degree 3

Rated surge voltage 8 kV

Insulation resistance min. 100 M Ω

Overvoltage category (EN 60664-1) I

Overvoltage category (EN 60950-1) III

Mechanical data

Holding force contacts min. 100 N

Holding force modules min. 240 N

Pulling force max. 220 N

Mechanical data | Material data

Coating contact silver-plated

Combustibility class (UL94) V-0

Material housing PA

Material contact Brass

Mechanical data | Mounting data

Number of module slots 1

Height 45,7 mm

Width 14,5 mm

Depth 34,4 mm

Environmental characteristics | Climatic

Operating temperature min. -40 °C

Operating temperature max. 125 °C

Climatic category (EN IEC 60068-1) 40/125/10