

Female module, 8-pole, crimp t.

400 V, 16 A


Female  
8-pole  
Crimp  
Technical data will be only guaranteed with Murrelektronik components.

Link a termékhez

Ábrák



Szimbolikus ábra



| Commercial data               |               |
|-------------------------------|---------------|
| ECLASS-6.0                    | 27143424      |
| ECLASS-6.1                    | 27261204      |
| ECLASS-7.0                    | 27440204      |
| ECLASS-8.0                    | 27440204      |
| ECLASS-9.0                    | 27440217      |
| ECLASS-10.1                   | 27440217      |
| ECLASS-11.1                   | 27440217      |
| ECLASS-12.0                   | 27440217      |
| ETIM-5.0                      | EC000438      |
| customs tariff number         | 85389099      |
| GTIN                          | 4048879641630 |
| Packaging unit                | 5             |
| Electrical data   Supply      |               |
| Operating voltage AC          | 400 V         |
| Operating voltage DC          | 400 V         |
| Operating current             | 16 A          |
| Installation                  |               |
| Connection cross section min. | 0,5 mm²       |
| Connection cross section max. | 4 mm²         |
| AWG number min.               | 20            |

AWG number max. 11

#### Installation | Connection

|                               |        |
|-------------------------------|--------|
| Wire insulation diameter min. | 4,6 mm |
| Connection                    | Crimp  |
| Gender                        | female |
| Mating cycles min.            | 500    |

#### Installation | Pin assignment

|              |   |
|--------------|---|
| No. of poles | 8 |
|--------------|---|

#### Device protection | Electrical

|                                   |        |
|-----------------------------------|--------|
| Pollution Degree                  | 3      |
| Rated surge voltage               | 6 kV   |
| Insulation resistance min.        | 100 MΩ |
| Overvoltage category (EN 60664-1) | I      |
| Overvoltage category (EN 60950-1) | III    |

#### Mechanical data

|                             |       |
|-----------------------------|-------|
| Holding force contacts min. | 130 N |
| Holding force modules min.  | 300 N |
| Pulling force max.          | 220 N |

#### Mechanical data | Material data

|                             |                       |
|-----------------------------|-----------------------|
| Coating contact             | versilbert, vergoldet |
| Combustibility class (UL94) | V-0                   |
| Material housing            | PA                    |
| Material contact            | Brass                 |

#### Mechanical data | Mounting data

|                        |         |
|------------------------|---------|
| Number of module slots | 1       |
| Height                 | 45,5 mm |
| Width                  | 14,5 mm |
| Depth                  | 34,4 mm |

#### Environmental characteristics | Climatic

|                                    |           |
|------------------------------------|-----------|
| Operating temperature min.         | -40 °C    |
| Operating temperature max.         | 125 °C    |
| Climatic category (EN IEC 60068-1) | 40/125/10 |