

MODL. VARIO 4-way coupling housing type B

nickel plated aluminum

Mobile housing (round)  
4-way  
Aluminium  
Screw locking  
Good chemical and oil resistance (oil resistance does not apply to use with PVC cable)  
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link a termékhez

Ábrák



Szimbolikus ábra

| Commercial data                        |                      |
|----------------------------------------|----------------------|
| ECLASS-6.0                             | 27260702             |
| ECLASS-6.1                             | 27260708             |
| ECLASS-7.0                             | 27440312             |
| ECLASS-8.0                             | 27440312             |
| ECLASS-9.0                             | 27440312             |
| ECLASS-10.1                            | 27440312             |
| ECLASS-11.1                            | 27440312             |
| ECLASS-12.0                            | 27440312             |
| ETIM-5.0                               | EC002641             |
| customs tariff number                  | 85389099             |
| GTIN                                   | 4048879572972        |
| Packaging unit                         | 1                    |
| Device protection   Electrical         |                      |
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68     |
| Degree of protection (ISO 20653:2013)  | IP66K, IP69K         |
| Additional condition protection degree | inserted, screwed    |
| Mechanical data                        |                      |
| Operating pressure min.                | -0,8 bar             |
| Operating pressure max.                | 16 bar               |
| Mechanical data   Material data        |                      |
| Coating housing                        | powder-coated        |
| Material housing                       | Aluminum die casting |
| Mechanical data   Mounting data        |                      |

|                 |              |
|-----------------|--------------|
| Mounting method | screw fixing |
|-----------------|--------------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 120 °C |