

**MODL. VARIO insert for coupling housing type B**

4/2 no shut-off, nickel plated brass

Insert - mobile housing  
Brass, nickel plated  
without shut-off  
AD4

[Link a termékhez](#)**Ábrák**

Szimbolikus ábra

**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27260702      |
| ECLASS-6.1            | 27260708      |
| ECLASS-7.0            | 27440312      |
| ECLASS-8.0            | 27440312      |
| ECLASS-9.0            | 27440312      |
| ECLASS-10.1           | 27440312      |
| ECLASS-11.1           | 27440312      |
| ECLASS-12.0           | 27440312      |
| ETIM-5.0              | EC002641      |
| customs tariff number | 74198090      |
| GTIN                  | 4048879572217 |
| Packaging unit        | 1             |

**Device protection | Electrical**

|                                        |                   |
|----------------------------------------|-------------------|
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68  |
| Degree of protection (ISO 20653:2013)  | IP66K, IP69K      |
| Additional condition protection degree | inserted, screwed |

**Mechanical data**

|                         |                  |
|-------------------------|------------------|
| Barrier                 | without shut-off |
| Operating pressure min. | -0,8 bar         |
| Operating pressure max. | 16 bar           |

**Mechanical data | Material data**

|                  |               |
|------------------|---------------|
| Coating housing  | nickel plated |
| Material gasket  | FPM           |
| Material housing | Brass         |

**Mechanical data | Mounting data**

|                     |      |
|---------------------|------|
| Outer diameter hose | 4 mm |
|---------------------|------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
|----------------------------|--------|

|                            |        |
|----------------------------|--------|
| Operating temperature max. | 120 °C |
|----------------------------|--------|