

MODL. VARIO insert for fixed housing type B

6/4 no shut-off, dezincification resistant brass

Modlink Vario  
Insert - stationary housing  
Brass, dezincification-resistant  
without shut-off  
AD6

Link a termékhez

Ábrák



Szimbolikus ábra

| Commercial data                        |                   |
|----------------------------------------|-------------------|
| ECLASS-6.0                             | 27260702          |
| ECLASS-6.1                             | 27260708          |
| ECLASS-7.0                             | 27440312          |
| ECLASS-8.0                             | 27440312          |
| ECLASS-9.0                             | 27440312          |
| ECLASS-10.1                            | 27440312          |
| ECLASS-11.1                            | 27440312          |
| ECLASS-12.0                            | 27440312          |
| ETIM-5.0                               | EC002641          |
| customs tariff number                  | 74198090          |
| GTIN                                   | 4048879572538     |
| Packaging unit                         | 1                 |
| Device protection   Electrical         |                   |
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68  |
| Degree of protection (ISO 20653:2013)  | IP66K, IP69K      |
| Additional condition protection degree | inserted, screwed |
| Mechanical data                        |                   |
| Barrier                                | without shut-off  |
| Operating pressure min.                | -0,8 bar          |
| Operating pressure max.                | 16 bar            |
| Mechanical data   Material data        |                   |
| Material gasket                        | FPM               |
| Material housing                       | Brass             |
| Mechanical data   Mounting data        |                   |

|                     |      |
|---------------------|------|
| Outer diameter hose | 6 mm |
|---------------------|------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
|----------------------------|--------|

|                            |        |
|----------------------------|--------|
| Operating temperature max. | 120 °C |
|----------------------------|--------|